



V.1.0 GB  
REV 06-07.2017.

**High Performance Additives**

# **MPEX®**

## **DPF REGENERATE**

### **Technical Datasheet**





V.1.0 GB  
REV 06-07.2017.

## High Performance Additives

### TDS

Colour/Type	Amber / DPF Regenerate
Areas of usage:	For all diesel engines (incl. common rail and turbo charged engines) with standard or retrofitted diesel particulate filter.
Environment:	Please check local requirements and MSDS
Packaging:	300ml Container
PPE:	Avoid skin contact. Refer to MSDS
Storage: Prevent	N/A
Surface prep:	None
Equipment needed:	None
Tests:	ISO9001. (For further information contact Leading Solvent Supplies Ltd)
Applying/Drying	Pour the contents of one bottle in the fuel tank before filling it with diesel
Origin/Manufacture:	Leading Solvent Supplies Ltd





V.1.0 GB  
REV 06-07.2017.

## High Performance Additives

## Useful Information

How to optimise the use of MPEX<sup>®</sup> DPF Regenerate

### Applications:

MPEX<sup>®</sup> DPF Regenerate is an organo-metallic diesel fuel additive to be used as a catalyst for the regeneration of diesel particulate filters. MPEX<sup>®</sup> DPF Regenerate Reduces ignition temperature of trapped soot ensuring extraordinary combustion at temperatures typically encountered during normal engine operation. Preventing performance loss caused by clogged diesel particulate filters additionally reducing particulate emission assisting in meeting strict legislation and emission limits, this extends the lifetime of the expensive diesel particulate filter. In addition regenerating the diesel particulate filters, 5-10 times faster and more complete than when using a catalyst coated diesel particulate filter. The unique combination of a clean fuel system, clean combustion with lower emissions and catalysed soot particles will assist in keeping the catalytic converter, exhaust gas recirculation system (EGR) as well as the turbo compressor and its variable geometry vanes clean from deposits.

### Method of use:

Pour the contents of one bottle in the fuel tank before filling it with diesel fuel.

### Dosage:

One bottle treats 40 to 60 litres of diesel fuel.

### IMPORTANT

MPEX<sup>®</sup> Are manufactured by Leading Solvent Supplies Ltd. MPEX<sup>®</sup> products information are based on laboratory tests and practical experience. Since the conditions under which the product is used are often outside the control of Leading Solvent Supplies Ltd, we can only guarantee the product quality, since the result is dependent on the substrate, pre-treatment, temperature, air humidity, application etc. Leading Solvent Supplies Ltd reserves the right, without notice to change the product and the given data.

[www.mpexdirect.com](http://www.mpexdirect.com)

Marston Business Park | Rudgate | Tockwith | YO26 7QF | United Kingdom  
t. 01423 358000 | e. [sales@mpexdirect.com](mailto:sales@mpexdirect.com) | w. [mpexdirect.com](http://www.mpexdirect.com)

