



# MPEX® Octane Booster

## Material Safety Data Sheet

Page 1 of 16  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revised on / Version: 07.03.2013 / 0003  
Replaces revision of / Version: 28.01.2011 / 0002  
Valid from: 07.03.2013  
PDF print date: 18.02.2014  
MPEX® Octane Booster (51022)

### Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1 Product identifier

**MPEX® Octane Booster (51022)**

##### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture:**

Additives

**Uses advised against:**

No information available at present.

##### 1.3 Details of the supplier of the safety data sheet

Leading Solvent Supplies Ltd, Marston Business Park, Rudgate, Tockwith, YO26 7QF United Kingdom  
Telephone: ++44 (0)1423 358000, Fax: ++44 (0)1423 222012  
www.mpexdirect.com

Qualified person's e-mail address: sales@mpexdirect.com Please DO NOT use for requesting Safety Data Sheets.

##### 1.4 Emergency telephone

**Emergency information services / official advisory body:**

---

**Telephone number of the company in case of emergencies:**

Tel.: ++44 (0)1423 358000 (9.00 - 17:00h)

#### SECTION 2: Hazards identification

##### 2.1 Classification of the substance or mixture

###### 2.1.1 Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Flam. Liq.	3	H226-Flammable liquid and vapour.
Asp. Tox.	1	H304-May be fatal if swallowed and enters airways.
Aquatic Chronic	3	H412-Harmful to aquatic life with long lasting effects.

###### 2.1.2 Classification according to Directives 67/548/EEC and 1999/45/EC (including amendments)

Flammable, R10  
Xn, Harmful, R65  
R66  
Dangerous for the environment, R52-53

##### 2.2 Label elements

###### 2.2.1 Labeling according to Regulation (EC) 1272/2008 (CLP)



# MPEX® Octane Booster

## Material Safety Data Sheet

Page 2 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revised on / Version: 07.03.2013 / 0003  
 Replaces revision of / Version: 28.01.2011 / 0002  
 Valid from: 07.03.2013  
 PDF print date: 18.02.2014  
 MPEX® Octane Booster (51022)



Danger

### Hazard statement

H226-Flammable liquid and vapour. H304-May be fatal if swallowed and enters airways. H412-Harmful to aquatic life with long lasting effects.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.

### Prevention

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P273-Avoid release to the environment.

### Response

P301+P310-IF SWALLOWED: Immediately call a POISON CENTER/doctor. P331-Do NOT induce vomiting.

### Disposal

P501-Dispose of contents/container in a safe way.

EUH066-Repeated exposure may cause skin dryness or cracking.

Naphtha (petroleum), hydrotreated heavy

## 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006.

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006.

## SECTION 3: Composition/information on ingredients

### 3.1 Substance

n.a.

### 3.2 Mixture

Naphtha (petroleum), hydrotreated heavy	
Registration number (REACH)	--
Index	649-327-00-6
EINECS, ELINCS, NLP	265-150-3
CAS	CAS 64742-48-9
content %	80-100
Classification according to Directive 67/548/EEC	Flammable, R10 Harmful, Xn, R65 R66
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 3, H226 Asp. Tox. 1, H304

Tricarbonyl(methylcyclopentadienyl)manganese	
Registration number (REACH)	--
Index	---
EINECS, ELINCS, NLP	235-166-5
CAS	CAS 12108-13-3



# MPEX<sup>®</sup> Octane Booster

## Material Safety Data Sheet

GB

Page 3 of 16  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revised on / Version: 07.03.2013 / 0003  
Replaces revision of / Version: 28.01.2011 / 0002  
Valid from: 07.03.2013  
PDF print date: 18.02.2014  
MPEX<sup>®</sup> Octane Booster (51022)

<b>content %</b>	1-<2,5
<b>Classification according to Directive 67/548/EEC</b>	Very toxic, T+, R26 Toxic, T, R24/25 Dangerous for the environment, N, R50-53
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Acute Tox. 3, H301 Acute Tox. 3, H311 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1) Acute Tox. 2, H330

<b>Solvent naphtha (petroleum), heavy arom.</b>	
<b>Registration number (REACH)</b>	--
<b>Index</b>	649-424-00-3
<b>EINECS, ELINCS, NLP</b>	265-198-5
<b>CAS</b>	CAS 64742-94-5
<b>content %</b>	0,1-<1
<b>Classification according to Directive 67/548/EEC</b>	Dangerous for the environment, N, R51 Dangerous for the environment, R53 Harmful, Xn, R65 R66 R67
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Aquatic Chronic 2, H411 Asp. Tox. 1, H304 STOT SE 3, H336

<b>1,2,4-trimethylbenzene</b>	<b>Substance for which an EU exposure limit value applies.</b>
<b>Registration number (REACH)</b>	--
<b>Index</b>	601-043-00-3
<b>EINECS, ELINCS, NLP</b>	202-436-9
<b>CAS</b>	CAS 95-63-6
<b>content %</b>	0,01-<1
<b>Classification according to Directive 67/548/EEC</b>	Flammable, R10 Harmful, Xn, R20 Irritant, Xi, R36/37/38 Dangerous for the environment, N, R51 Dangerous for the environment, R53
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Flam. Liq. 3, H226 Acute Tox. 4, H332 Eye Irrit. 2, H319 STOT SE 3, H335 Skin Irrit. 2, H315 Aquatic Chronic 2, H411

<b>Naphthalene</b>	<b>Substance for which an EU exposure limit value applies.</b>
<b>Registration number (REACH)</b>	--
<b>Index</b>	601-052-00-2
<b>EINECS, ELINCS, NLP</b>	202-049-5
<b>CAS</b>	CAS 91-20-3
<b>content %</b>	0,01-<1
<b>Classification according to Directive 67/548/EEC</b>	Harmful, Xn, R22 Carcinogen, R40, Carc.Cat.3 Dangerous for the environment, N, R50 Dangerous for the environment, R53
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Carc. 2, H351 Acute Tox. 4, H302 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410

For the text of the R-phrases / H-phrases and classification codes (GHS/CLP), see Section 16.



# MPEX® Octane Booster

## Material Safety Data Sheet

GB

Page 4 of 16  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revised on / Version: 07.03.2013 / 0003  
Replaces revision of / Version: 28.01.2011 / 0002  
Valid from: 07.03.2013  
PDF print date: 18.02.2014  
MPEX® Octane Booster (51022)

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

Never pour anything into the mouth of an unconscious person!  
Medical supervision necessary due to possibility of delayed reaction.

##### Inhalation

Remove person from danger area.  
Supply person with fresh air and consult doctor according to symptoms.  
If the person is unconscious, place in a stable side position and consult a doctor.  
Respiratory arrest - Artificial respiration apparatus necessary.

##### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap. Call a doctor immediately, keep datasheet at hand

##### Eye contact

Remove contact lenses.  
Wash thoroughly for several minutes using copious water - call doctor immediately, have Data Sheet available.

##### Ingestion

Rinse the mouth thoroughly with water.  
Do not induce vomiting. Consult doctor immediately.  
In case of vomiting, keep head low so that the stomach content does not reach the lungs.

#### 4.2 Most important symptoms and effects, both acute and delayed

Irritation of the eyes  
Product removes fat.  
Dermatitis (skin inflammation)  
Ingestion:  
Danger of aspiration  
Lung damage  
Inhalation:  
headaches  
irritation of the respiratory tract  
nausea  
Dizziness  
Effects/damages the central nervous system  
Mental confusion  
Coordination disorders  
In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Gastric lavage (stomach washing) only under endotracheal intubation.  
Subsequent observation for pneumonia and pulmonary oedema.

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

##### Suitable extinguishing media

CO2  
Extinction powder  
Foam  
Water jet spray

##### Unsuitable extinguishing media

High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:  
Oxides of carbon  
Manganese oxides  
Toxic pyrolysis products.  
Explosive vapour/air mixture  
Dangerous vapours heavier than air.



# MPEX® Octane Booster

## Material Safety Data Sheet

GB

Page 5 of 16  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revised on / Version: 07.03.2013 / 0003  
Replaces revision of / Version: 28.01.2011 / 0002  
Valid from: 07.03.2013  
PDF print date: 18.02.2014  
MPEX® Octane Booster (51022)

In case of spreading near the ground, flashback to distance sources of ignition is possible.

### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.  
Protective respirator with independent air supply.  
According to size of fire  
Full protection, if necessary  
Cool container at risk with water.  
Dispose of contaminated extinction water according to official regulations.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke.  
Ensure sufficient supply of air.  
If air supply is not sufficient, wear protective breathing apparatus.  
Avoid inhalation, and contact with eyes or skin.  
If applicable, caution - risk of slipping

### 6.2 Environmental precautions

If leakage occurs, dam up.  
Resolve leaks if this possible without risk.  
Prevent surface and ground-water infiltration, as well as ground penetration.  
Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.  
If accidental entry into drainage system occurs, inform responsible authorities.

### 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.  
Fill the absorbed material into lockable containers.

### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

## SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

### 7.1 Precautions for safe handling

#### 7.1.1 General recommendations

Ensure good ventilation.  
Avoid inhalation of the vapours.  
If applicable, suction measures at the workstation or on the processing machine necessary.  
Keep away from sources of ignition - Do not smoke.  
Take measures against electrostatic charging, if appropriate.  
Avoid contact with eyes or skin.  
Handle and open container with care.  
Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.  
Observe directions on label and instructions for use.  
Use working methods according to operating instructions.

#### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.  
Wash hands before breaks and at end of work.  
Keep away from food, drink and animal feedingstuffs.  
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.  
Store product closed and only in original packing.  
Not to be stored in gangways or stair wells.  
Observe special storage conditions (in Germany, e.g., in accordance with the regulations in the "Betriebssicherheitsverordnung").  
Solvent resistant floor  
Do not store with oxidizing agents.  
Store in a well ventilated place.  
Protect from direct sunlight and warming.  
Store cool



# MPEX® Octane Booster

## Material Safety Data Sheet

Page 6 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revised on / Version: 07.03.2013 / 0003  
 Replaces revision of / Version: 28.01.2011 / 0002  
 Valid from: 07.03.2013  
 PDF print date: 18.02.2014  
 MPEX® Octane Booster (51022)

### 7.3 Specific end use(s)

No information available at present.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):  
 1200 mg/m<sup>3</sup>

<b>Chemical Name</b>	Naphtha (petroleum), hydrotreated heavy		Content %:80-100
WEL-TWA: 1200 mg/m <sup>3</sup> (>= C7 normal and branched chain alkanes)	WEL-STEL: ---	---	
BMGV: ---	Other information: ---		
<b>Chemical Name</b>	Solvent naphtha (petroleum), heavy arom.		Content %:0,1-<1
WEL-TWA: 500 mg/m <sup>3</sup> (Aromatics)	WEL-STEL: ---	---	
BMGV: ---	Other information: ---		
<b>Chemical Name</b>	1,2,4-trimethylbenzene		Content %:0,01-<1
WEL-TWA: 25 ppm (125 mg/m <sup>3</sup> ) (Trimethylbenzenes, all isomers or mixtures) (WEL), 20 ppm (100 mg/m <sup>3</sup> ) (EU)	WEL-STEL: ---	---	
BMGV: ---	Other information: ---		
<b>Chemical Name</b>	Naphthalene		Content %:0,01-<1
WEL-TWA: 10 ppm (50 mg/m <sup>3</sup> ) (EU)	WEL-STEL: ---	---	
BMGV: ---	Other information: ---		

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

\*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

1,2,4-trimethylbenzene						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	100	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	100	mg/m <sup>3</sup>	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	16171	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	100	mg/m <sup>3</sup>	
Workers / employees	Human - blood	Long term, local effects	DNEL	100	mg/m <sup>3</sup>	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	29,4	mg/m <sup>3</sup>	
Consumer	Human - inhalation	Long term, local effects	DNEL	29,4	mg/m <sup>3</sup>	
Consumer	Human - dermal	Long term, systemic effects	DNEL	9512	mg/kg bw/day	



# MPEX® Octane Booster

## Material Safety Data Sheet

Page 7 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 07.03.2013 / 0003

Replaces revision of / Version: 28.01.2011 / 0002

Valid from: 07.03.2013

PDF print date: 18.02.2014

MPEX® Octane Booster (51022)

Consumer	Human - inhalation	Long term, systemic effects	DNEL	29,4	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	15	mg/kg bw/d	
Consumer	Human - inhalation	Long term, local effects	DNEL	29,4	mg/m3	
	Environment - freshwater		PNEC	0,12	mg/l	
	Environment - marine		PNEC	0,12	mg/l	
	Environment - sewage treatment plant		PNEC	2,41	mg/l	
	Environment - sediment, freshwater		PNEC	13,56	mg/kg dry weight	
	Environment - sediment, marine		PNEC	13,56	mg/kg dry weight	
	Environment - soil		PNEC	2,34	mg/kg dry weight	

Naphthalene						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	3,57	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	25	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	25	mg/m3	
	Environment - freshwater		PNEC	2,4	µg/l	
	Environment - marine		PNEC	0,24	µg/l	
	Environment - sewage treatment plant		PNEC	2,9	mg/l	
	Environment - sediment, freshwater		PNEC	67200	mg/kg dry weight	
	Human - oral		PNEC	67200	mg/kg dry weight	
	Environment - soil		PNEC	53300	mg/kg dry weight	

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Solvent resistant protective gloves (EN 374).

If applicable

Protective nitrile gloves (EN 374)

Protective gloves made of polyvinyl alcohol (EN 374)

Protective Viton® / fluoroelastomer gloves (EN 374)





# MPEX® Octane Booster

## Material Safety Data Sheet

Page 8 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 07.03.2013 / 0003

Replaces revision of / Version: 28.01.2011 / 0002

Valid from: 07.03.2013

PDF print date: 18.02.2014

MPEX® Octane Booster (51022)

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments)

Respiratory protection:

If OES or MEL is exceeded.

Gas mask filter A (EN 14387), code colour brown

At high concentrations:

Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138)

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

If applicable, these are included in the individual protective measures (eye/face protection, skin protection, respiratory protection).

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Amber, Clear
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	~40 °C
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	0,776 g/ml
Bulk density:	Not determined
Solubility(ies):	Not determined
Water solubility:	Not determined
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Viscosity:	<7 mm <sup>2</sup> /s (40°C)
Explosive properties:	Not determined
Oxidising properties:	Not determined

### 9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined





# MPEX® Octane Booster

## Material Safety Data Sheet

CE

Page 9 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revised on / Version: 07.03.2013 / 0003  
 Replaces revision of / Version: 28.01.2011 / 0002  
 Valid from: 07.03.2013  
 PDF print date: 18.02.2014  
 MPEX® Octane Booster (51022)

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

See also Subsection 10.2 to 10.6.  
 The product has not been tested.

#### 10.2 Chemical stability

See also Subsection 10.1 to 10.6.  
 Stable with proper storage and handling.

#### 10.3 Possibility of hazardous reactions

See also Subsection 10.1 to 10.6.  
 Possible build up of flammable vapour/air mixture.

#### 10.4 Conditions to avoid

See also section 7.  
 Heating, open flame, ignition sources  
 Electrostatic charge

#### 10.5 Incompatible materials

See also section 7.  
 Avoid contact with strong oxidizing agents.

#### 10.6 Hazardous decomposition products

See also Subsection 10.1 to 10.5.  
 See also section 5.2  
 No decomposition when used as directed.

### SECTION 11: Toxicological information

Possibly more information on health effects, see Section 2.1 (classification).

#### MPEX® Octane Booster (51022)

Toxicity/effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	>5000,00	mg/kg	Rat		calculated value
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit		Additive for motor oil
Acute toxicity, by inhalation:	LD50	>5,43	mg/l/4h	Rat		Additive for motor oil
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Respiratory tract irritation:						n.d.a.
Repeated dose toxicity:						n.d.a.
Symptoms:						n.d.a.
Other information:						Classification according to calculation procedure.

#### Naphtha (petroleum), hydrotreated heavy

Toxicity/effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat		



# MPEX® Octane Booster

## Material Safety Data Sheet

Page 10 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 07.03.2013 / 0003

Replaces revision of / Version: 28.01.2011 / 0002

Valid from: 07.03.2013

PDF print date: 18.02.2014

MPEX® Octane Booster (51022)

Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC50	>5	mg/l/4h	Rat		
Skin corrosion/irritation:						Repeated exposure may cause skin dryness or cracking.
Aspiration hazard:						Yes
Symptoms:						unconsciousness, headaches, dizziness

### Tricarbonyl(methylcyclopentadienyl)manganese

Toxicity/effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	58-175	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	140-795	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC50	0,247	mg/l/1h	Rat		
Acute toxicity, by inhalation:	LC50	0,076	mg/l/4h	Rat		
Germ cell mutagenicity (in vivo):	NOAL			Mouse		Negative
Reproductive toxicity:	NOEL	30,2	µg/l			
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAL	0,3	µg/l	Rat		

### Solvent naphtha (petroleum), heavy arom.

Toxicity/effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC50	>5	mg/l/4h	Rat		
Skin corrosion/irritation:						Repeated exposure may cause skin dryness or cracking. Mild irritant
Serious eye damage/irritation:						
Respiratory or skin sensitisation:				Guinea pig		Not sensitizing
Aspiration hazard:						Yes
Symptoms:						dizziness, headaches, drowsiness, dizziness

### 1,2,4-trimethylbenzene

Toxicity/effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat		
Acute toxicity, by inhalation:	LC50	18	mg/l/4h	Rat		
Symptoms:						dizziness, unconsciousness, headaches, fatigue, dizziness, nausea

### Naphthalene

Toxicity/effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	490	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2500	mg/kg	Rat		
Acute toxicity, by inhalation:	LC50	>110	mg/l/4h			



# MPEX® Octane Booster

## Material Safety Data Sheet

GB

Page 11 of 16  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revised on / Version: 07.03.2013 / 0003  
 Replaces revision of / Version: 28.01.2011 / 0002  
 Valid from: 07.03.2013  
 PDF print date: 18.02.2014  
 MPEX® Octane Booster (51022)

Symptoms:							lack of appetite, ataxia, breathing difficulties, unconsciousness, diarrhoea, cornea opacity, headaches, cramps, gastrointestinal disturbances, mucous membrane irritation, dizziness, nausea and vomiting.
-----------	--	--	--	--	--	--	---

### SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

MPEX® Octane Booster (51022)							
Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:							n.d.a.
Toxicity to daphnia:							n.d.a.
Toxicity to algae:							n.d.a.
Persistence and degradability:							n.d.a.
Bioaccumulative potential:							n.d.a.
Mobility in soil:							n.d.a.
Results of PBT and vPvB assessment:							n.d.a.
Other adverse effects:							n.d.a.

Naphtha (petroleum), hydrotreated heavy							
Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:	LC50	96h	>100	mg/l			
Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna		
Persistence and degradability:		28d	70	%			Readily biodegradable
Bioaccumulative potential:	Log Pow		5 - 6,7				

Tricarbonyl(methylcyclopentadienyl)manganese							
Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to daphnia:	EC50	48h	0,83	mg/l			
Persistence and degradability:							
Water solubility:			29	mg/l			

Solvent naphtha (petroleum), heavy arom.							
Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:	LC50	96h	1-10	mg/l			
Toxicity to daphnia:	EC50	48h	1-10	mg/l			
Toxicity to algae:	IC50	72h	1-10	mg/l			
Persistence and degradability:							Not readily biodegradable
Bioaccumulative potential:	Log Pow		>3,8-4,8				
Bioaccumulative potential:	BCF		<100				
Other information:	BOD		52	%			

1,2,4-trimethylbenzene							
Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:	LC50	96h	7,72	mg/l			



# MPEX® Octane Booster

## Material Safety Data Sheet

Page 12 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 07.03.2013 / 0003

Replaces revision of / Version: 28.01.2011 / 0002

Valid from: 07.03.2013

PDF print date: 18.02.2014

MPEX® Octane Booster (51022)

Toxicity to daphnia:	EC50	48h	3,6	mg/l		
----------------------	------	-----	-----	------	--	--

Naphthalene							
Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:	LC50	96h	1,99	mg/l	Pimephales promelas		
Toxicity to daphnia:	EC50	48h	2,19	mg/l	Daphnia magna		
Toxicity to algae:	LC50	4h	2,96	mg/l	Selenastrum capricornutum		
Other information:	BOD5		0	%			
Other information:	COD		22	%			

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2001/118/EC, 2001/119/EC, 2001/573/EC)

13 07 03 other fuels (including mixtures)

Recommendation:

Pay attention to local and national official regulations

Implement substance recycling.

E.g. suitable incineration plant.

#### For contaminated packing material

Pay attention to local and national official regulations

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

Do not perforate, cut up or weld uncleaned container.

Residues may present a risk of explosion.

## SECTION 14: Transport information

### General statements

UN number: 1993

#### Transport by road/by rail (ADR/RID)

UN proper shipping name:

UN 1993 FLAMMABLE LIQUID, N.O.S. (NAPHTHA (PETROLEUM),1,2,4-TRIMETHYL BENZENE) (SPECIAL PROVISION 640E)

Transport hazard class(es): 3

Packing group: III

Classification code: F1

LQ (ADR 2013): 5 L

LQ (ADR 2009): 7

Environmental hazards: Not applicable

Tunnel restriction code: D/E

#### Transport by sea (IMDG-code)

UN proper shipping name:

FLAMMABLE LIQUID, N.O.S. (NAPHTHA (PETROLEUM),1,2,4-TRIMETHYL BENZENE)

Transport hazard class(es): 3

Packing group: III

EmS: F-E, S-E

Marine Pollutant: n.a

Environmental hazards: Not applicable

#### Transport by air (IATA)

UN proper shipping name:

Flammable liquid, n.o.s. (NAPHTHA (PETROLEUM),1,2,4-TRIMETHYL BENZENE)





# MPEX® Octane Booster

## Material Safety Data Sheet

GB

Page 13 of 16  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revised on / Version: 07.03.2013 / 0003  
 Replaces revision of / Version: 28.01.2011 / 0002  
 Valid from: 07.03.2013  
 PDF print date: 18.02.2014  
 MPEX® Octane Booster (51022)

Transport hazard class(es): 3  
 Packing group: III  
 Environmental hazards: Not applicable

### Special precautions for user

Persons employed in transporting dangerous goods must be trained.  
 All persons involved in transporting must observe safety regulations.  
 Precautions must be taken to prevent damage.

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.  
 Minimum amount regulations have not been taken into account.  
 Danger code and packing code on request.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

For classification and labelling see Section 2.

Observe restrictions: Yes  
 Comply with trade association/occupational health regulations.  
 Observe youth employment law (German regulation).  
 Observe law on protection of expectant mothers (German regulation).  
 Regulation (EC) No 1907/2006, Annex XVII  
 VOC 1999/13/EC: ~ 98,5 w/w%

### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

## SECTION 16: Other information

These details refer to the product as it is delivered.  
 Revised sections: 1, 2, 15

### Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Flam. Liq. 3, H226	Classification based on test data.
Asp. Tox. 1, H304	Classification according to calculation procedure.
Aquatic Chronic 3, H412	Classification according to calculation procedure.

The following phrases represent the posted R phrases / H phrases, Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

- 10 Flammable.
- 20 Harmful by inhalation.
- 22 Harmful if swallowed.
- 24/25 Toxic in contact with skin and if swallowed.
- 26 Very toxic by inhalation.
- 36/37/38 Irritating to eyes, respiratory system and skin.
- 40 Limited evidence of a carcinogenic effect.
- 50 Very toxic to aquatic organisms.
- 50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 51 Toxic to aquatic organisms.
- 52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 53 May cause long-term adverse effects in the aquatic environment.
- 65 Harmful: may cause lung damage if swallowed.
- 66 Repeated exposure may cause skin dryness or cracking.
- 67 Vapours may cause drowsiness and dizziness.
- H330 Fatal if inhaled.
- H226 Flammable liquid and vapour.



# MPEX® Octane Booster

## Material Safety Data Sheet

Page 14 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 07.03.2013 / 0003

Replaces revision of / Version: 28.01.2011 / 0002

Valid from: 07.03.2013

PDF print date: 18.02.2014

MPEX® Octane Booster (51022)

H301 Toxic if swallowed.  
H302 Harmful if swallowed.  
H304 May be fatal if swallowed and enters airways.  
H311 Toxic in contact with skin.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H351 Suspected of causing cancer.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.  
H411 Toxic to aquatic life with long lasting effects.

Flam. Liq. — Flammable liquid  
Asp. Tox. — Aspiration hazard  
Aquatic Chronic — Hazardous to the aquatic environment - chronic  
Acute Tox. — Acute toxicity - oral  
Acute Tox. — Acute toxicity - dermal  
Aquatic Acute — Hazardous to the aquatic environment - acute  
Acute Tox. — Acute toxicity - inhalation  
STOT SE — Specific target organ toxicity - single exposure - narcotic effects  
Eye Irrit. — Eye irritation  
STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation  
Skin Irrit. — Skin irritation  
Carc. — Carcinogenicity

### Any abbreviations and acronyms used in this document:

AC Article Categories  
acc., acc. to according, according to  
ACGIH American Conference of Governmental Industrial Hygienists  
ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)  
AOEL Acceptable Operator Exposure Level  
AOX Adsorbable organic halogen compounds  
approx. approximately  
Art., Art. no. Article number  
ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)  
BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)  
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)  
BCF Bioconcentration factor  
BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)  
BHT Butylhydroxytoluol (= 2,6-Di-*t*-butyl-4-methyl-phenol)  
BMGV Biological monitoring guidance value (EH40, UK)  
BOD Biochemical oxygen demand  
BSEF Bromine Science and Environmental Forum  
bw body weight  
CAS Chemical Abstracts Service  
CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids  
CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques  
CIPAC Collaborative International Pesticides Analytical Council  
CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)  
CMR carcinogenic, mutagenic, reproductive toxic  
COD Chemical oxygen demand  
CTFA Cosmetic, Toiletry, and Fragrance Association  
DMEL Derived Minimum Effect Level  
DNEL Derived No Effect Level  
DOC Dissolved organic carbon



# MPEX® Octane Booster

## Material Safety Data Sheet

Page 15 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 07.03.2013 / 0003

Replaces revision of / Version: 28.01.2011 / 0002

Valid from: 07.03.2013

PDF print date: 18.02.2014

MPEX® Octane Booster (51022)

DT50 Dwell Time - 50% reduction of start concentration  
DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)  
dw dry weight  
e.g. for example (abbreviation of Latin 'exempli gratia'), for instance  
EC European Community  
ECHA European Chemicals Agency  
EEA European Economic Area  
EEC European Economic Community  
EINECS European Inventory of Existing Commercial Chemical Substances  
ELINCS European List of Notified Chemical Substances  
EN European Norms  
EPA United States Environmental Protection Agency (United States of America)  
ERC Environmental Release Categories  
ES Exposure scenario  
etc. et cetera  
EU European Union  
EWC European Waste Catalogue  
Fax. Fax number  
gen. general  
GHS Globally Harmonized System of Classification and Labelling of Chemicals  
GWP Global warming potential  
HET-CAM Hen's Egg Test - Chorionallantoic Membrane  
HGWP Halocarbon Global Warming Potential  
IARC International Agency for Research on Cancer  
IATA International Air Transport Association  
IBC Intermediate Bulk Container  
IBC (Code) International Bulk Chemical (Code)  
IC Inhibitory concentration  
IMDG-code International Maritime Code for Dangerous Goods  
incl. including, inclusive  
IUCLID International Uniform Chemical Information Database  
LC lethal concentration  
LC50 lethal concentration 50 percent kill  
LCLo lowest published lethal concentration  
LD Lethal Dose of a chemical  
LD50 Lethal Dose, 50% kill  
LDLo Lethal Dose Low  
LOAEL Lowest Observed Adverse Effect Level  
LOEC Lowest Observed Effect Concentration  
LOEL Lowest Observed Effect Level  
LQ Limited Quantities  
MARPOL International Convention for the Prevention of Marine Pollution from Ships  
n.a. not applicable  
n.av. not available  
n.c. not checked  
n.d.a. no data available  
NIOSH National Institute of Occupational Safety and Health (United States of America)  
NOAEC No Observed Adverse Effective Concentration  
NOAEL No Observed Adverse Effect Level  
NOEC No Observed Effect Concentration  
NOEL No Observed Effect Level  
ODP Ozone Depletion Potential  
OECD Organisation for Economic Co-operation and Development  
org. organic  
PAH polycyclic aromatic hydrocarbon  
PBT persistent, bioaccumulative and toxic  
PC Chemical product category  
PE Polyethylene  
PNEC Predicted No Effect Concentration  
POCP Photochemical ozone creation potential  
ppm parts per million  
PROC Process category





# MPEX® Octane Booster

## Material Safety Data Sheet

Page 16 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 07.03.2013 / 0003

Replaces revision of / Version: 28.01.2011 / 0002

Valid from: 07.03.2013

PDF print date: 18.02.2014

MPEX® Octane Booster (51022)

PTFE Polytetrafluorethylene

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SADT Self-Accelerating Decomposition Temperature

SAR Structure Activity Relationship

SU Sector of use

SVHC Substances of Very High Concern

Tel. Telephone

ThOD Theoretical oxygen demand

TOC Total organic carbon

TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).

WHO World Health Organization

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

**Leading Solvent Supplies Ltd, Marston Business Park, Rudgate, Tockwith, YO26 7QF United Kingdom**

**Tel: +44 (0)1423 358000, Fax: +44 (0)1423 222012**

© by Leading Solvent Supplies Ltd. The copying or changing of this document is forbidden except with consent from Leading Solvent Supplies Ltd.

*DISCLAIMER OF LIABILITY The information in this MSDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness*